

**FEATURES**

- ◆ For 12V lead-acid batteries with capacity 1,5 Ah - 4 Ah
- ◆ Float and cyclic charging mode
- ◆ Charging state signaled by LEDS
- ◆ Short-circuit and overload protection
- ◆ Reverse polarity protection
- ◆ Does not require supervision
- ◆ Wide range of supply voltage
- ◆ Cables included

**TECHNICAL DATA**

Model	LC-2302
Supply voltage	100~240 [VAC]
Supply frequency	50~60 [Hz]
Input power	13 [W]
Output voltage	10~15 [VDC]
Output power	6 [W]
Max charging current	0,4 [A]
Charging voltage	14,7 [VDC]
Float charging voltage	13,65 [VDC]
Work temperature	0~40 [°C]
Weight	175 [g]
Dimensions	82x56x47

**EUROPOWER** charger works in three stages. The cycle starts with charging the battery with maximum, constant current. After reaching appropriate level of voltage by the battery, the constant voltage charging is started. The green led lights when the charging ends. The battery is fully charged and ready to disconnect, the charger enters trickle charge mode. The battery is constantly maintained in fully charged state and the connection period of the charger isn't restricted.

**LEDS**

- Power, float charge
- Fast charge

**MANUFACTURER**

EMU Sp. z o.o. Sp. k.  
ul. Twarda 12  
80-871 Gdańsk  
(058) 344 04 01-03  
info@emu.com.pl

